

## **ASMZGxxxxA058L13**

### **SMA Male to TNC- Male Low Loss Cable**



#### **Key Features**

- SMA Male to TNC Male
- LLC200A - Low loss cable
- Cable extension for panel mount outdoor antennas
- Suitable for low RF signal level locations

#### **General Description**

Connector: SMA Male to TNC Male

Cable: Low loss (LLC200A - see specification below)



Cable length: ASMZG300A058L13 - 3M

ASMZG500A058L13 - 5M

ASMZG1000A058L13 - 10M

ASMZG1500A058L13 - 15M

#### **Cable Data**



# ASMZGxxxxA058L13

## SMA Male to TNC- Male Low Loss Cable

### Cable Construction

Item			Unit	Coaxial Cable
Main conductor:	Diameter:		mm	0.94
	Material:		-	Bare copper wire
Insulation:	Diameter:		mm	2.79
	Material:		-	GAS-FPE
	Colour:		-	Nature
Shield:	Tape:	Material:	-	Bonded aluminium foil
		Composition:	-	16 x 4
	Braid:	Diameter:	mm	0.01 ± 0.008
		Material:	-	Tinned copper
Jacket:	Diameter:		mm	4.95
	Material:		-	RoHS PVC
	Colour:		-	Black

### Electrical Characteristics

Item	Unit	Standard
Conductor resistance:	Ω/km	24.9 ↓
Insulation resistance:	MΩ/km	1000 ↑
Withstanding voltage:	V/Min	1000
Normal impedance:	Ω	50 ± 3
Normal capacitance:	pF/m	83.3

### Attenuation v. Frequency


Frequency (MHz)	30	150	450	900	1500	1800	2400	3000
Attenuation dB/100M:	6.5	14.6	25.5	36.5	47.7	52.5	62.4	64.0

## ASMZGxxxxA058L13


### SMA Male to TNC- Male Low Loss Cable

#### Graphs


##### Impedance Result



##### Return Loss Result



##### SWR Result



##### Insertion Loss Graphic

