


8	GASKET	1	SILICONE	NICKEL
7	WASHER	1	STEEL	NICKEL
6	RETAINING RING	1	BE Cu	NICKEL
5	SHELL	2	BRASS	NICKEL
4	GROUND RING	1	BRASS	NICKEL
3	INSULATOR	1	TEFLON	NONE
2	PIN	1	BRASS	GOLD
1	BODY	1	BRASS	NICKEL
NO	Description	Q'ty	Material	Finish

<b>UNLESS OTHERWISE SPECIFIED</b> 1.REMOVE ALL BURRS. 2.BREAK ALL CONNERS & EDGES CO.15 MAX. 3.CHAMFER 1ST & LAST THREADS 45°. 4.DIAMETERS ON COMMON CENTERS. TO BE CONCENTRIC WITHIN 0.1 T.I.R. 5.ALL DIMENSIONS ARE AFTER PLATING.	<b>* MAJOR DIMENSION</b>				APPROVED	 <b>Siretta</b> Enabling Industrial IoT	
	UNLESS OTHERWISE NOTED TOLERANCES 0.5-6=±0.2 6-30=±0.4 30-120=±0.6 120-315=±1.0 ANGLES=±1°				CHECKED		
	SCALE 3/1 UNIT MM				DRAWN andrew	TITLE QMA PLUG TO SMA PLUG	REV A
	DRAWN DATE 02/06/02				FILE NO.	DRAWING NO. ADAPT/QMAM/SMAM	