

## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna



### Key Features

- Operates between 600 MHz – 6000 MHz
- Supports 5G NR/ 4G LTE/ Cat M/ NB-IoT/ 3G UMTS
- Supports Dual band Wi-Fi 2.4G & 5G
- High efficiency Dipole Terminal Antenna
- Terminated with N-Type (M) connector
- IP67 waterproof enclosure

### Additional Considerations

- Omnidirectional radiation pattern
- Ground Plane independent

### General Description

The Delta 53 is a high-efficiency, wideband dipole antenna covering a wide frequency range from 600 MHz to 6000 MHz. Optimised for peak performance across the 1800 MHz to 5200 MHz band, it supports the full spectrum of sub-6 GHz 5G NR, 4G LTE, legacy cellular, Wi-Fi, and ISM bands.

Engineered for reliable outdoor deployment, the Delta 53 features a durable IP67-rated housing and is supplied with an N-Type (M) connector for direct mounting on industrial gateways, wireless routers, and telemetry devices.

Its high efficiency and makes it ideal for applications requiring long-term connectivity across diverse wireless technologies.

### Typical Applications

- Industrial routers and cellular gateways
- Outdoor wireless telemetry systems
- Smart city infrastructure, lighting, and waste management
- Building and perimeter security for LTE/5G-connected cameras

D Direct	5G New Radio	4G LTE	3G UMTS	2G GSM	LTE M
LTE NB-IoT	NR NB-IoT	IEEE 802.15.4	ISM 433	ISM 868	ISM 915
ISM 2.4G	ISM 5.8G	WiFi 2.4G & 5G	WiFi 5 802.11ac	WiFi 6 802.11ax	WiFi 6e 802.11ax
WLAN 2400	WLAN 5800	BLE Bluetooth	ZB Zigbee	SF Sigfox	HNT Helium
UWB Ultra-Wideband	IP 67				



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Electrical Specifications

Frequency range:	600-960 MHz, 1500-6000 MHz
Impedance:	50 $\Omega$
Polarisation:	Linear
Average gain:	2.9 dBi
Peak gain:	6.43 dBi
Average spherically integrated total gain:	600-960 MHz: -2.10 dBi 1500-5900 MHz: -1.79 dBi
Average efficiency:	~60%
VSWR:	<2.5
Input power	1 W
Directionality:	Omni-directional
Ground plane independent:	Yes

### Environmental Specifications

Operating temperature range:	-40 °C to +85 °C
Storage temperature range:	-40 °C to +85 °C


### Mechanical Specifications

Colour options:	Black
Connector options:	N-type Male
Mounting method:	Direct connect
Dimensions:	178 mm Length x $\varnothing$ 21 mm
Weight:	71 g
Radome:	Thermoplastic Rubber (TPR)

## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Dimensional Drawing






## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Spectrum Coverage







## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Peak Gain vs. Frequency



### VSWR






## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Radiation Efficiency





## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Usable Cellular Frequency Support (400 MHz – 2000 MHz)

	400	410	450	600	700	800	850	900	1500	1600	1700	1800	1900	2000
GSM Bands:							●	●						
UMTS Bands:					●	●	●	●	●		●			
LTE Bands:				●	●	●	●	●	●	●	●		●	●
LTE Cat M Bands:				●	●	●	●	●	●	●	●			
LTE Cat NB Bands:				●	●	●	●	●	●	●	●			●
5G NR Bands:				●	●	●	●	●	●	●	●	●		●
NR Cat NB Bands:				●	●	●	●	●	●	●				●
NTN Bands:										●				●

### Usable Cellular Frequency Support (2100 MHz – 6700 MHz)

	2100	2300	2400	2500	2600	3300	3500	3700	4700	5200	5900	6000	6200	6700
GSM Bands:														
UMTS Bands:	●				●		●							
LTE Bands:	●	●	●	●	●	●	●	●		●				
LTE Cat M Bands:	●	●		●	●		●	●						
LTE Cat NB Bands:	●			●	●		●	●						
5G NR Bands:	●	●	●	●	●		●	●		●				
NR Cat NB Bands:	●			●	●									
NTN Bands:					●									



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Usable ISM Frequency Support (433 MHz - 6525 MHz)

	433	868	915	2450	5800	6525
Bluetooth			●	●		
Helium		●	●			
IEEE 802.15.4		●	●	●		
ISM 433			●			
ISM 868		●	●			
ISM 915			●			
ISM 2.4G				●		
ISM 5.8G						
LoRa		●	●			
SigFox		●	●			
Weightless		●	●			
Wi-Fi 2.4G				●		
Wi-Fi 5G						
Wi-Fi 6E					●	
Zigbee		●	●	●		
Z-Wave		●	●			



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Cellular Standards Band Support

GSM (2G) Band	UMTS (3G) Band	E-UTRA (4G) Band	Cat M E-UTRA Band	Cat NB E-UTRA Band	NR (5G) Band	Cat NB NR (5G) Band	NTN Band	Uplink	Downlink	Average Upload Efficiency (%)	Average Download Efficiency (%)	Maximum Upload VSWR	Maximum Download VSWR	Use Indicator
	1	1	1	1	n1	n1		1920 - 1980 MHz	2110 - 2170 MHz	42.92	52.13	2.62	2.78	●
PCS-1900	2	2	2	2	n2	n2		1850 - 1910 MHz	1930 - 1990 MHz	16.94	47.25	3.13	2.44	●
DCS-1800	3	3	3	3	n3	n3		1710 - 1785 MHz	1805 - 1880 MHz	46.09	20.29	2.87	3.13	●
	4	4	4	4				1710 - 1755 MHz	2110 - 2155 MHz	47.80	52.75	2.87	2.64	●
GSM-850	5	5	5	5	n5	n5		824 - 849 MHz	869 - 894 MHz	56.04	48.37	1.26	1.17	●
	6							830 - 840 MHz	875 - 885 MHz	56.61	48.36	1.24	1.14	●
	7	7	7	7	n7	n7		2500 - 2570 MHz	2620 - 2690 MHz	71.43	79.72	1.52	1.60	●
E-GSM-900	8	8	8	8	n8	n8		880 - 915 MHz	925 - 960 MHz	48.67	41.36	1.11	1.64	●
	9	9						1749.9 - 1784.9 MHz	1844.9 - 1879.9 MHz	43.85	14.66	2.34	3.13	●
	10	10						1710 - 1770 MHz	2110 - 2170 MHz	46.63	52.13	2.87	2.78	●
	11	11	11	11				1427.9 - 1447.9 MHz	1475.9 - 1495.9 MHz	57.62	52.33	2.82	2.54	●
	12	12	12	12	n12	n12		699 - 716 MHz	729 - 746 MHz	62.49	68.06	1.33	1.26	●
	13	13	13	13	n13			777 - 787 MHz	746 - 756 MHz	72.53	68.88	1.20	1.21	●
	14	14	14	14	n14	n14		788 - 798 MHz	758 - 768 MHz	71.23	69.65	1.22	1.20	●
		17		17				704 - 716 MHz	734 - 746 MHz	62.98	68.45	1.33	1.24	●
		18	18	18	n18	n18		815 - 830 MHz	860 - 875 MHz	61.95	47.39	1.28	1.22	●
	19	19	19	19				830 - 845 MHz	875 - 890 MHz	55.57	48.48	1.24	1.14	●
	20	20	20	20	n20	n20		832 - 862 MHz	791 - 821 MHz	51.85	67.83	1.24	1.28	●
	21	21	21	21				1447.9 - 1462.9 MHz	1495.9 - 1510.9 MHz	55.61	53.31	2.70	2.45	●
	22	22						3410 - 3490 MHz	3510 - 3590 MHz	63.68	64.50	1.99	2.03	●
		24	24	24	n24	n24		1626.5 - 1660.5 MHz	1525 - 1559 MHz	61.75	57.05	2.09	2.32	●
	25	25	25	25	n25	n25		1850 - 1915 MHz	1930 - 1995 MHz	17.65	48.32	3.13	2.44	●
	26	26	26	26	n26	n26		814 - 849 MHz	859 - 894 MHz	58.14	48.02	1.28	1.22	●
		27	27					807 - 824 MHz	852 - 869 MHz	64.68	47.70	1.28	1.24	●
		28	28	28	n28	n28		703 - 748 MHz	758 - 803 MHz	65.85	71.10	1.33	1.24	●

● Suitable band

● Adequate band in good signal conditions

● Likely to be unsuitable



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Cellular Standards Band Support

GSM (2G) Band	UMTS (3G) Band	E-UTRA (4G) Band	Cat M E-UTRA Band	Cat NB E-UTRA Band	NR (5G) Band	Cat NB NR (5G) Band	NTN Band	Uplink	Downlink	Average Upload Efficiency (%)	Average Download Efficiency (%)	Maximum Upload VSWR	Maximum Download VSWR	Use Indicator
		28A						703 - 733 MHz	758 - 788 MHz	64.56	71.23	1.33	1.20	●
		29			n29			N/A	717 - 728 MHz	N/A	65.47	N/A	1.33	●
		30			n30			2305 - 2315 MHz	2350 - 2360 MHz	54.87	53.40	2.84	2.35	●
		31	31	31	n31	n31		452.5 - 457.5 MHz	462.5 - 467.5 MHz	10.48	9.83	25.76	26.38	●
	32	32						N/A	1452 - 1496 MHz	N/A	53.47	N/A	2.66	●
		33						1900 - 1920 MHz	1900 - 1920 MHz	24.99	24.99	2.93	2.93	●
		34			n34			2010 - 2025 MHz	2010 - 2025 MHz	64.82	64.82	1.28	1.28	●
		35						1850 - 1910 MHz	1850 - 1910 MHz	16.94	16.94	3.13	3.13	●
		36						1930 - 1990 MHz	1930 - 1990 MHz	47.25	47.25	2.44	2.44	●
		37						1910 - 1930 MHz	1910 - 1930 MHz	29.39	29.39	2.78	2.78	●
		38			n38			2570 - 2620 MHz	2570 - 2620 MHz	76.81	76.81	1.53	1.53	●
		39	39		n39			1880 - 1920 MHz	1880 - 1920 MHz	21.43	21.43	3.11	3.11	●
		40	40		n40			2300 - 2400 MHz	2300 - 2400 MHz	53.56	53.56	2.87	2.87	●
		41	41	41	n41	n41		2496 - 2690 MHz	2496 - 2690 MHz	75.69	75.69	1.60	1.60	●
		42	42	42				3400 - 3600 MHz	3400 - 3600 MHz	64.06	64.06	2.03	2.03	●
		43	43	43				3600 - 3800 MHz	3600 - 3800 MHz	77.16	77.16	2.01	2.01	●
		44						703 - 803 MHz	703 - 803 MHz	68.52	68.52	1.33	1.33	●
		45						1447 - 1467 MHz	1447 - 1467 MHz	55.38	55.38	2.70	2.70	●
		46			n46			5150 - 5925 MHz	5150 - 5925 MHz	57.27	57.27	3.74	3.74	●
		47			n47			5855 - 5925 MHz	5855 - 5925 MHz	41.01	41.01	3.74	3.74	●
		48	48	48	n48			3550 - 3700 MHz	3550 - 3700 MHz	73.08	73.08	2.03	2.03	●
		49						3550 - 3700 MHz	3550 - 3700 MHz	73.08	73.08	2.03	2.03	●
		50			n50			1432 - 1517 MHz	1432 - 1517 MHz	54.39	54.39	2.80	2.80	●
		51			n51			1427 - 1432 MHz	1427 - 1432 MHz	58.54	58.54	2.83	2.83	●
		52						3300 - 3400 MHz	3300 - 3400 MHz	62.73	62.73	1.93	1.93	●

● Suitable band

● Adequate band in good signal conditions

● Likely to be unsuitable



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Cellular Standards Band Support

GSM (2G) Band	UMTS (3G) Band	E-UTRA (4G) Band	Cat M E-UTRA Band	Cat NB E-UTRA Band	NR (5G) Band	Cat NB NR (5G) Band	NTN Band	Uplink	Downlink	Average Upload Efficiency (%)	Average Download Efficiency (%)	Maximum Upload VSWR	Maximum Download VSWR	Use Indicator
		53			n53			2483.5 - 2495 MHz	2483.5 - 2495 MHz	63.01	63.01	1.42	1.42	●
		54	54	54	n54	n54		1670 - 1675 MHz	1670 - 1675 MHz	61.09	61.09	2.00	2.00	●
		65		65	n65	n65		1920 - 2010 MHz	2110 - 2200 MHz	49.13	52.34	2.62	3.04	●
		66	66	66	n66	n66		1710 - 1780 MHz	2110 - 2200 MHz	46.27	52.34	2.87	3.04	●
		67			n67			N/A	738 - 758 MHz	N/A	68.82	N/A	1.23	●
		68						698 - 728 MHz	753 - 783 MHz	63.61	70.69	1.33	1.20	●
		69						N/A	2570 - 2620 MHz	N/A	76.81	N/A	1.53	●
		70		70	n70	n70		1695 - 1710 MHz	1995 - 2020 MHz	50.73	64.53	2.78	1.42	●
		71	71	71	n71	n71		663 - 698 MHz	617 - 652 MHz	65.35	62.29	1.32	1.71	●
		72	72	72	n72	n72		451 - 456 MHz	461 - 466 MHz	10.47	10.04	25.70	26.22	●
		73	73	73				450 - 455 MHz	460 - 465 MHz	10.45	10.19	25.66	26.11	●
		74	74	74	n74	n74		1427 - 1470 MHz	1475 - 1518 MHz	56.36	53.07	2.83	2.54	●
		75			n75			N/A	1432 - 1517 MHz	N/A	54.39	N/A	2.80	●
		76			n76			N/A	1427 - 1432 MHz	N/A	58.54	N/A	2.83	●
					n77			3300 - 4200 MHz	3300 - 4200 MHz	73.96	73.96	2.03	2.03	●
					n78			3300 - 3800 MHz	3300 - 3800 MHz	69.03	69.03	2.03	2.03	●
					n79			4400 - 5000 MHz	4400 - 5000 MHz	70.61	70.61	2.14	2.14	●
					n80			1710 - 1785 MHz	N/A	46.09	N/A	2.87	N/A	●
					n81			880 - 915 MHz	N/A	48.67	N/A	1.11	N/A	●
					n82			832 - 862 MHz	N/A	51.85	N/A	1.24	N/A	●
					n83			703 - 748 MHz	N/A	65.85	N/A	1.33	N/A	●
					n84			1920 - 1980 MHz	N/A	42.92	N/A	2.62	N/A	●
		85	85	85	n85			698 - 716 MHz	728 - 746 MHz	62.43	67.98	1.33	1.26	●
					n86			1710 - 1780 MHz	N/A	46.27	N/A	2.87	N/A	●
		87	87	87				410 - 415 MHz	420 - 425 MHz	9.54	9.80	23.39	24.59	●

● Suitable band

● Adequate band in good signal conditions

● Likely to be unsuitable



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Cellular Standards Band Support

GSM (2G) Band	UMTS (3G) Band	E-UTRA (4G) Band	Cat M E-UTRA Band	Cat NB E-UTRA Band	NR (5G) Band	Cat NB NR (5G) Band	NTN Band	Uplink	Downlink	Average Upload Efficiency (%)	Average Download Efficiency (%)	Maximum Upload VSWR	Maximum Download VSWR	Use Indicator
		88	88	88				412 - 417 MHz	422 - 427 MHz	9.59	9.86	23.50	24.61	●
					n89			824 - 849 MHz	N/A	56.04	N/A	1.26	N/A	●
					n90	n90		2496 - 2690 MHz	2496 - 2690 MHz	75.69	75.69	1.60	1.60	●
					n91			832 - 862 MHz	1427 - 1432 MHz	51.85	58.54	1.24	2.83	●
					n92			832 - 862 MHz	1432 - 1517 MHz	51.85	54.39	1.24	2.80	●
					n93			880 - 915 MHz	1427 - 1432 MHz	48.67	58.54	1.11	2.83	●
					n94			880 - 915 MHz	1432 - 1517 MHz	48.67	54.39	1.11	2.80	●
					n95			2010 - 2025 MHz	N/A	64.82	N/A	1.28	N/A	●
					n97			2300 - 2400 MHz	N/A	53.56	N/A	2.87	N/A	●
					n98			1880 - 1920 MHz	N/A	21.43	N/A	3.11	N/A	●
					n99			1626.5 - 1660.5 MHz	N/A	61.75	N/A	2.09	N/A	●
1900					n101			1900 - 1910 MHz	1900 - 1910 MHz	22.80	22.80	2.93	2.93	●
		103		103				787 - 788 MHz	757 - 758 MHz	71.96	68.98	1.20	1.19	●
					n105			663 - 703 MHz	612 - 652 MHz	64.84	61.71	1.32	1.76	●
							n254	1610 - 1625.5 MHz	2483.5 - 2500 MHz	59.10	63.79	2.10	1.43	●
							n255	1626.5 - 1660.5 MHz	1525 - 1559 MHz	61.75	57.05	2.09	2.32	●
							n256	1980 - 2010 MHz	2170 - 2200 MHz	61.55	52.76	1.62	3.04	●

● Suitable band

● Adequate band in good signal conditions

● Likely to be unsuitable

**NOTE:** For each frequency band, Siretta provides a traffic light indication to show the suitability of the antenna for use at that frequency band. Determination of exactly what makes an antenna good or bad at any frequency is subjective.

The view presented is that of Siretta's engineering team having taken into account the efficiency and VSWR measurements. The end user is advised to use their own criteria and/or testing to confirm suitability.



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### ISM Standards Frequency Support

Application	Frequency Range	Efficiency (%)	Maximum VSWR	Peak Gain from highest direction (dBi)	Use Indicator
ISM 433 MHz	433.05 - 434.79 MHz	10.13	24.54	-5.11	●
ISM 868 MHz	863 - 870 MHz	47.31	1.20	3.87	●
ISM 915 MHz	902 - 928 MHz	47.62	1.23	4.63	●
ISM 2.4 GHz	2400 - 2500 MHz	58.29	1.69	2.98	●
Wi-Fi 2.4G	2401 - 2483 MHz	57.23	1.68	2.98	●
Wi-Fi 2.4G (USA)	2401 - 2473 MHz	56.83	1.68	2.98	●
Wi-Fi 2.4G (Japan)	2401 - 2495 MHz	57.96	1.68	2.98	●
Wi-Fi 5G (all channels)	5150 - 5990 MHz	55.94	3.74	6.65	●
Wi-Fi 5G (Ch 32-48)	5150 - 5250 MHz	72.86	1.98	6.65	●
Wi-Fi 5G (Ch 32-64)	5150 - 5330 MHz	72.02	1.98	6.65	●
Wi-Fi 5G (Ch 32-161)	5150 - 5815 MHz	59.87	3.50	6.65	●
Wi-Fi 5G (Ch 32-173)	5150 - 5875 MHz	58.41	3.73	6.65	●
ISM 5.8 GHz	5725 - 5875 MHz	44.58	3.73	3.55	●
UWB band 1	3168 - 3696 MHz	67.23	2.03	3.09	●
UWB band 2	3696 - 4224 MHz	79.51	1.95	3.67	●
UWB band 3	4224 - 4752 MHz	70.42	2.14	4.18	●
UWB band 4	4752 - 5280 MHz	72.46	2.07	6.65	●
UWB band 5	5280 - 5808 MHz	56.96	3.44	6.48	●

● Suitable band

● Adequate band in good signal conditions

● Likely to be unsuitable

**NOTE:** For each frequency band, Siretta provides a traffic light indication to show the suitability of the antenna for use at that frequency band. Determination of exactly what makes an antenna good or bad at any frequency is subjective.


The view presented is that of Siretta's engineering team having taken into account the efficiency and VSWR measurements. The end user is advised to use their own criteria and/or testing to confirm suitability.



## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Test Setup (in Free Space)






## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 600 MHz XY




#### XZ




#### YZ




#### 700 MHz XY




#### XZ




#### YZ




#### 800 MHz XY



#### XZ



#### YZ




## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 850 MHz XY




#### XZ




#### YZ




#### 868 MHz XY




#### XZ




#### YZ




#### 900 MHz XY



#### XZ



#### YZ






## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 915 MHz XY




#### XZ




#### YZ




#### 1500 MHz XY




#### XZ




#### YZ




#### 1600 MHz XY



#### XZ



#### YZ






## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 1700 MHz XY




#### XZ




#### YZ




#### 1800 MHz XY




#### XZ




#### YZ




#### 1900 MHz XY



#### XZ



#### YZ






## IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 2400 MHz XY




#### XZ




#### YZ




#### 2437 MHz XY




#### XZ




#### YZ




#### 2442 MHz XY



#### XZ



#### YZ




## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 2448 MHz XY




#### XZ




#### YZ




#### 2450 MHz XY




#### XZ




#### YZ




#### 2500 MHz XY



#### XZ



#### YZ






# Delta 53


## IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

## 2D Radiation Plots


**2600 MHz XY**




**XZ**




YZ




**3300 MHz XY**




XZ




YZ




**3432 MHz XY**



XZ



YZ






## IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 4488 MHz XY




#### XZ




#### YZ




#### 4900 MHz XY




#### XZ




#### YZ




#### 5016 MHz XY



#### XZ



#### YZ






## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 2D Radiation Plots


#### 5512 MHz XY




#### XZ




#### YZ




#### 5544 MHz XY




#### XZ




#### YZ




#### 5570 MHz XY



#### XZ



#### YZ




## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 3D Radiation Plots


600 MHz




700 MHz




800 MHz




850 MHz




868 MHz




900 MHz




915 MHz



1500 MHz



1600 MHz




## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 3D Radiation Plots


1700 MHz




1800 MHz




1900 MHz




2000 MHz




2100 MHz




2300 MHz




2400 MHz



2437 MHz



2442 MHz




## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 3D Radiation Plots


2448 MHz




2450 MHz




2500 MHz




2600 MHz




3300 MHz




3432 MHz




3500 MHz



3700 MHz



3960 MHz






## Delta 53


IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### 3D Radiation Plots


4488 MHz




4900 MHz




5016 MHz




5200 MHz




5240 MHz




5482 MHz




5512 MHz



5544 MHz



5570 MHz



**NOTE:** All 3D radiation plots are shown with Theta = 45 and Phi = 45.





## Delta 53

IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna

### Ordering Details:

Part Number	Description
DELTA53/X/NTYPE-M/S/S/32	IP67 N-Type Male Wideband 5G/4G and Wi-Fi Terminal Mount Antenna