



6	PIN	1	Be Cu	GOLD	<b>UNLESS OTHERWISE SPECIFIED</b> 1.REMOVE ALL BURRS. 2.BREAK ALL CONNERS & EDGES CO.15 MAX. 3.CHAMFER 1ST & LAST THREADS 45°. 4.DIAMETERS ON COMMON CENTERS. TO BE CONCENTRIC WITHIN 0.1 T.I.R. 5.ALL DIMENSIONS ARE AFTER PLATING.	<b>* MAJOR DIMENSION</b> UNLESS OTHERWISE NOTED TOLERANCES 0.5-6=±0.2 6-30=±0.4 30-120=±0.6 120-315=±1.0 ANGLES=±1°	APPROVED	HF		
5	INSULATOR	1	TEFLON	NONE			CHECKED	HF		<b>TITLE</b> SMA MALE TO REVERSE POLARITY SMA MALE
4	BODY	1	BRASS	GOLD						<b>DRAWING NO.</b> ADAPT/SMAM/SMAM/RP
3	WASHER	2	Be Cu	None						
2	GASKET	2	SILICONE	NONE						
1	SHELL	2	Brass	GOLD						
NO	Description	Q'ty	Material	Finish		SCALE	3/1	UNIT	MM	