


5	GASKET	1	Si-rubber	NONE	UNLESS OTHERWISE SPECIFIED 1.REMOVE ALL BURRS. 2.BREAK ALL CONNERS & EDGES CO.15 MAX. 3.CHAMFER 1ST & LAST THREADS 45°. 4.DIAMETERS ON COMMON CENTERS. TO BE CONCENTRIC WITHIN 0.1 T.I.R. 5.ALL DIMENSIONS ARE AFTER PLATING.	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES 0.5-6=±0.2 6-30=±0.4 30-120=±0.6 120-315=±1.0 ANGLES=±1°				APPROVED Paul		<div> Siretta Enabling Industrial IoT</div> <div>TITLE SMA MALE TO SMA FEMALE REVERSE POLARITY</div> <div>DRAWING NO. ADAPT/SMAM/SMAF/RP</div>	
4	SHELL	1	BRASS	NICKEL						CHECKED Harry			
3	DIELECTRIC	1	TEFLON	NONE						DRAWN Andrew			
2	PIN	1	BRASS	GOLD		SCALE 3/1 UNIT MM				DRAWN DATE 03/12/02			
1	BODY	1	BRASS	NICKEL									
NO	Description	Q'ty	Material	Finish									